

DELOS 2 TRIO

MAIN CHARACTERISTICS

Applications	Street and urban lighting.
Optic	<p>STU-M/S: Asymmetrical optic for street, urban and cycle-path lighting. STE-M/S: Asymmetrical optic for suburban street lighting. STW: Asymmetrical optic for wide urban and suburban road lighting, specific for wet asphalts. S05: Asymmetrical optic for street, urban and green areas lighting. OP-DX/SX: Asymmetrical optic for crosswalks lighting. Colour temperature: 4000K (3000K optional) CRI ≥ 70 Photobiological safety class: EXEMPT GROUP LED source efficiency: 168 lm/W @ 525mA, Tj=85°C, 4000K</p>
Insulation class	II, I
Protection degree	IP66 IK08 total
Tilt angle	0°
Mounting	Installation on MPD brackets
Gear tray	Removable
LED modules	Removable/Replaceable
Dimensions	Ø626x273mm - See the drawing
Weight	max. 12 kg
Exposed surface	Side: 0.10m ² Top: 0.31m ²
Operating temperature	-40°C / +35°C
Storage temperature	-40°C / +80°C
Main reference standards	EN 60598-1, EN 60598-2-3, EN 62471, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3





ELECTRICAL CHARACTERISTICS

Rated voltage	220÷240V 50/60Hz
Power factor	>0,9 (at full load)
On-load switch	Included, with integrated cable clamp.
Mains connection	Connector for cables max section 4mm ²
Surge protection	Up to 10kV With SPD (optional) 10kV / 10kV CM/DM
SPD (optional)	10kV-10kA, type II, with LED signal and thermo fuse to disconnect load at the end of life.
Control system (options)	<p>F: Fixed power not dimmerable. DA: Automatic dimming (virtual midnight) with default profile. DAC: Custom DA profile. FLC: Constant light flux. DALI: Digital dimming interface DALI.</p>
Optical unit lifetime (Tq=25°C, 700mA)	<p>>100.000hr L90B10 >100.000hr L90, TM-21</p>

MATERIALS

Fixing	Die-cast aluminium UNI EN 1706
Body	Aluminium
Heatsink	Extruded aluminum.
Lower frame	Die-cast aluminium UNI EN 1706
Optic	99.85% aluminum with a surface finish in 99.95% with vacuum-sealed deposition. Aluminum grade class A+ (DIN EN 16268)
Screen	Flat tempered glass, 4mm thickness high transparency
Cable gland	Plastic M20x1,5 - IP68
Gasket	EPDM
Colour	Graphite - Cod. 01

DA Profile



STU-M Optic

All the published photometrical data has been obtained according to EN 13032-1





LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
DELOS 2 0F2H1 4.5-1M	S05 STU-M STU-S	1840	16	115	2184	13
DELOS 2 0F2H1 4.5-2M		3620	30.5	118	4368	26
DELOS 2 0F2H1 4.5-3M		5420	44	123	6552	39
DELOS 2 0F2H1 4.5-4M		7010	57	122	8736	52
DELOS 2 0F2H1 4.7-1M	S05 STU-M STU-S	2370	21.5	110	2765	18
DELOS 2 0F2H1 4.7-2M		4630	40	115	5530	36
DELOS 2 0F2H1 4.7-3M		6890	58	118	8295	54
DELOS 2 0F2H1 4.7-4M		8810	76	115	11060	72
DELOS 2 0F3 4.5-1M	STE-M STE-S STW	2560	21.5	119	2950	17
DELOS 2 0F3 4.5-2M		5060	39	129	5900	34
DELOS 2 0F3 4.5-3M		7340	57	128	8850	51
DELOS 2 0F3 4.5-4M		9750	76	128	11800	68
DELOS 2 0F3 4.7-1M	STE-M STE-S STW	3200	28	114	3735	24
DELOS 2 0F3 4.7-2M		6400	52	123	7470	48
DELOS 2 0F3 4.7-3M		9230	76	121	11205	72
DELOS 2 0F3 4.7-4M		12300	102	120	14940	96
DELOS 2 0F6 4.5-1M	OP-DX	5060	39	129	5900	34
DELOS 2 0F6 4.5-2M	OP-SX	9750	76	128	11800	68
DELOS 2 0F6 4.7-1M	OP-DX	6400	52	123	7470	48
DELOS 2 0F6 4.7-2M	OP-SX	12300	102	120	14940	96

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±5%.

The characteristics of the product listed above are subjected to change without notice.



LUMINAIRE	OPTIC	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
DELOS 2 0F2H1 3.5-1M		1720	16	107	1990	13
DELOS 2 0F2H1 3.5-2M	S05 STU-M STU-S	3360	30.5	110	3980	26
DELOS 2 0F2H1 3.5-3M		5040	44	114	5970	39
DELOS 2 0F2H1 3.5-4M		6520	57	114	7960	52
DELOS 2 0F2H1 3.7-1M		2210	21.5	102	2520	18
DELOS 2 0F2H1 3.7-2M	S05 STU-M STU-S	4300	40	107	5040	36
DELOS 2 0F2H1 3.7-3M		6410	58	110	7560	54
DELOS 2 0F2H1 3.7-4M		8190	76	107	10080	72
DELOS 2 0F3 3.5-1M		2380	21.5	110	2701	17
DELOS 2 0F3 3.5-2M	STE-M STE-S STW	4700	39	120	5402	34
DELOS 2 0F3 3.5-3M		6830	57	119	8103	51
DELOS 2 0F3 3.5-4M		9070	76	119	10804	68
DELOS 2 0F3 3.7-1M		2980	28	106	3420	24
DELOS 2 0F3 3.7-2M	STE-M STE-S STW	5950	52	114	6840	48
DELOS 2 0F3 3.7-3M		8580	76	112	10260	72
DELOS 2 0F3 3.7-4M		11440	102	112	13680	96
DELOS 2 0F6 3.5-1M	OP-DX	4700	39	120	5402	34
DELOS 2 0F6 3.5-2M	OP-SX	9070	76	119	10804	68
DELOS 2 0F6 3.7-1M	OP-DX	5950	52	114	6840	48
DELOS 2 0F6 3.7-2M	OP-SX	11440	102	112	13680	96

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±5%.

The characteristics of the product listed above are subjected to change without notice.