**MOD2.0****MOD 2.0 BOLLARD****MAIN CHARACTERISTICS**


Applications	Urban and architectural lighting.
Optic	S05: Asymmetrical optic for street, urban and green areas lighting. Colour temperature: 4000K (3000K optional) CRI ≥ 70 Photobiological safety class: EXEMPT GROUP LED source efficiency: 177 lm/W @ 350mA, Tj=85°C, 4000K
Insulation class	II, I
Protection degree	IP66 IK08 total
Dimensions	See the table
Weight	MOD 2.0 BOLLARD 500 max 11.2kg MOD 2.0 BOLLARD 1000 max 19kg
Mounting	Fixing with plate
LED Modules	Removable / Replaceable
Gear tray	Removable
Operating temp.	-40°C / +50°C
Storage temp.	-40°C / +80°C
Main reference standards	EN 60598-1, EN 60598-2-3, EN 62471, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3

**ELECTRICAL CHARACTERISTICS**

Rated voltage	220÷240V 50/60Hz
Power factor	>0,95 (at full load - F, DA, DAC)
Mains connection	Cable H07RN-F nx1.5mm ² with connector M/F IP66/68 for cables max. 2.5mm ²
Surge protection	Up to 10kV With SPD (optional) 10kV / 10kV CM/DM
SPD (optional)	10kV-10kA, type 2+3, with LED signal and thermo fuse to disconnect load at the end of life.
Control system (options)	F: Fixed power not dimmable. DA: Automatic dimming (virtual midnight) with default profile. DAC: Custom DA profile. FLC: Constant light flux. WL: Wireless single point communication system. DALI: Digital dimming interface DALI.
Optical unit lifetime (Tq=25°C, 700mA)	>100.000hr L90B10 >100.000hr L90, TM-21

MATERIALS

Heat-sink	Die-cast aluminium UNI EN1706 powder painted.
Optic	99.85% aluminium with a surface finish in 99.95% with vacuum-sealed deposition. Aluminium grade class A+ (DIN EN 16268)
Profile	Extruded aluminium. Powder painted.
Fixing plate	Galvanized steel. Powder painted.
Screen	Flat tempered glass 5mm thickness satin.
Cable gland	Plastic M20x1.5 - IP68
Gasket	Polyurethane
Colour	Graphite - Cod. 01

**S05 Optic**

All the published photometrical data has been obtained according to applicable international standards

GREENLIGHT



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
MOD 2.0 BOLLARD 0F2H1 S05 4.3-1M SAT	S05	350	1050	11	95	1520	8

LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
MOD 2.0 BOLLARD 0F2H1 S05 3.3-1M SAT	S05	350	980	11	89	1386	8

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: $\pm 7\%$. Power tolerance: $\pm 5\%$.

The characteristics of the product listed above are subjected to change without notice.