



LF/LS 28/29 iBox

MAIN CHARACTERISTICS

Applications	Street and urban lighting
Optic	<p>STE-M/S: Asymmetrical optic for suburban street lighting. STU-M/S: Asymmetrical optic for street, urban and cycle-path lighting. STW: Asymmetrical optic for wide urban and suburban road lighting, specific for wet asphalts. SV/SV2: Asymmetrical optic for very narrow urban streets or highway entrance/exit turns. S05: Asymmetrical optic for street, urban and green areas lighting. S: Symmetrical optic for urban lighting and green areas. TS: Symmetrical optic for centre road lighting. Colour temperature: 4000K (3000K optional) CRI ≥ 70 Photobiological safety class: EXEMPT GROUP LED source efficiency: 168 lm/W @ 525mA, Tj=85°C, 4000K</p>
Insulation class	II, I
Protection degree	Optical unit: IP66 Driver: IP67 IK08
Tilt angle	0°
Installation	LF28/29: pole top installation for 1/2" GAS male. LS28/29: suspended installation for 1/2" GAS female.
Gear tray	Removable
Dimensions & weight	LF28/29: 530x460x820mm LS28/29: 530x460x930mm – max. 13 kg
Exposed surface	Side: 0.20m ² – Top: 0.19m ²
Operating temp.	-40°C / +35°C
Storage temperature	-40°C / +80°C
Main reference	EN 60598-1, EN 60598-2-3, EN 62471, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3



ELECTRICAL CHARACTERISTICS

Rated voltage	220÷240V 50/60Hz
Power factor	>0,9 (at full load)
Mains Connection	Cable: H05RN-F 2/3x1mm ² Optional: connector M/F IP66/68 for cables max. 2,5mm ² , Ø max. 12mm
Surge protection	CL. II: 8kV / 10kV CM/DM CL. I: 10kV / 10kV CM/DM (optional)
Control system (optional)	F: Fixed power not dimmable. DA: Automatic dimming (virtual midnight) with default profile. DAC: Custom DA profile. FLC: Constant light flux. D10: Dimming interface with 1-10V signal.
Optical unit lifetime (Ta=25°C, 700mA)	>100.000hr L90B10 >100.000hr L90, TM-21

MATERIALS

Fixing	LF28/29: Brass. LS28/29: Stainless steel tube.
Body	LF/LS28: Profiles: steel, upper dome: aluminium. LF/LS29: Profiles: brass, upper dome: copper.
Heatsink	Die-cast aluminum UNI EN1706 powder painted.
Optic	99.85% aluminum with a surface finish in 99.95% with vacuum-sealed deposition. Aluminum grade class A+ (DIN EN 16268)
Screen	Flat tempered glass, 4mm thickness PCG
Colour	LF/LS28: Graphite - Cod. 01 LF/LS29: Brass



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
LF-LS 28-29 iBox 0F2H1 4.5-1M PCG	S05	525	1430	16.5	86	2184	13
LF-LS 28-29 iBox 0F2H1 4.5-2M PCG	STU-M		2800	31	90	4368	26
LF-LS 28-29 iBox 0F2H1 4.5-3M PCG	STU-S		4200	45	93	6552	39
LF-LS 28-29 iBox 0F2H1 4.5-4M PCG	SV SV2 TS		5430	58	93	8736	52
LF-LS 28-29 iBox 0F2H1 4.7-1M PCG	S05	700	1840	22	83	2765	18
LF-LS 28-29 iBox 0F2H1 4.7-2M PCG	STU-M		3590	41	87	5530	36
LF-LS 28-29 iBox 0F2H1 4.7-3M PCG	STU-S		5340	59	90	8295	54
LF-LS 28-29 iBox 0F2H1 4.7-4M PCG	SV SV2 TS		6830	77.5	88	11060	72
LF-LS 28-29 iBox 0F3 4.5-1M PCG	STE-M STE-S STW	525	1980	22	90	2950	17
LF-LS 28-29 iBox 0F3 4.5-2M PCG			3920	40	98	5900	34
LF-LS 28-29 iBox 0F3 4.5-3M PCG			5690	58	98	8850	51
LF-LS 28-29 iBox 0F3 4.5-4M PCG			7560	77.5	97	11800	68
LF-LS 28-29 iBox 0F3 4.7-1M PCG	STE-M	700	2490	28.5	87	3735	24
LF-LS 28-29 iBox 0F3 4.7-2M PCG	STE-S		4960	53	93	7470	48
LF-LS 28-29 iBox 0F3 4.7-3M PCG	STW		7160	77.5	92	11205	72
LF-LS 28-29 iBox 0F3 4.5-1M PCG	S05	525	1880	22	85	2950	17
LF-LS 28-29 iBox 0F3 4.5-2M PCG			3730	40	93	5900	34
LF-LS 28-29 iBox 0F3 4.5-3M PCG			5410	58	93	8850	51
LF-LS 28-29 iBox 0F3 4.5-4M PCG			7180	77.5	92	11800	68
LF-LS 28-29 iBox 0F3 4.7-1M PCG	S05	700	2360	28.5	82	3735	24
LF-LS 28-29 iBox 0F3 4.7-2M PCG			4710	53	88	7470	48
LF-LS 28-29 iBox 0F3 4.7-3M PCG			6800	77.5	87	11205	72



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
LF-LS 28-29 iBox 0F2H1 4.5-2M PCG	S	525	2800	31	90	4368	26
LF-LS 28-29 iBox 0F2H1 4.5-4M PCG			5430	58	93	8736	52
LF-LS 28-29 iBox 0F2H1 4.7-2M PCG	S	700	3590	41	87	5530	36
LF-LS 28-29 iBox 0F2H1 4.7-4M PCG			6830	77.5	88	11060	72

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±10%.

The characteristics of the product listed above are subjected to change without notice.



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
LF-LS 28-29 iBox 0F2H1 3.5-1M PCG	S05	525	1330	16.5	80	1990	13
LF-LS 28-29 iBox 0F2H1 3.5-2M PCG	STU-M		2600	31	83	3980	26
LF-LS 28-29 iBox 0F2H1 3.5-3M PCG	STU-S		3910	45	86	5970	39
LF-LS 28-29 iBox 0F2H1 3.5-4M PCG	SV SV2 TS		5050	58	87	7960	52
LF-LS 28-29 iBox 0F2H1 3.7-1M PCG	S05	700	1710	22	77	2520	18
LF-LS 28-29 iBox 0F2H1 3.7-2M PCG	STU-M		3340	41	81	5040	36
LF-LS 28-29 iBox 0F2H1 3.7-3M PCG	STU-S		4970	59	84	7560	54
LF-LS 28-29 iBox 0F2H1 3.7-4M PCG	SV SV2 TS		6350	77.5	81	10080	72
LF-LS 28-29 iBox 0F3 3.5-1M PCG	STE-M STE-S STW	525	1840	22	83	2701	17
LF-LS 28-29 iBox 0F3 3.5-2M PCG			3650	40	91	5402	34
LF-LS 28-29 iBox 0F3 3.5-3M PCG			5290	58	91	8103	51
LF-LS 28-29 iBox 0F3 3.5-4M PCG			7030	77.5	90	10804	68
LF-LS 28-29 iBox 0F3 3.7-1M PCG	STE-M	700	2320	28.5	81	3420	24
LF-LS 28-29 iBox 0F3 3.7-2M PCG	STE-S		4610	53	86	6840	48
LF-LS 28-29 iBox 0F3 3.7-3M PCG	STW		6660	77.5	85	10260	72
LF-LS 28-29 iBox 0F3 3.5-1M PCG	S05	525	1750	22	79	2701	17
LF-LS 28-29 iBox 0F3 3.5-2M PCG			3470	40	86	5402	34
LF-LS 28-29 iBox 0F3 3.5-3M PCG			5030	58	86	8103	51
LF-LS 28-29 iBox 0F3 3.5-4M PCG			6680	77.5	86	10804	68
LF-LS 28-29 iBox 0F3 3.7-1M PCG	S05	700	2190	28.5	76	3420	24
LF-LS 28-29 iBox 0F3 3.7-2M PCG			4380	53	82	6840	48
LF-LS 28-29 iBox 0F3 3.7-3M PCG			6320	77.5	81	10260	72



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
LF-LS 28-29 iBox 0F2H1 3.5-2M PCG	S	525	2600	31	83	3980	26
LF-LS 28-29 iBox 0F2H1 3.5-4M PCG			5050	58	87	7960	52
LF-LS 28-29 iBox 0F2H1 3.7-2M PCG	S	700	3340	41	81	5040	36
LF-LS 28-29 iBox 0F2H1 3.7-4M PCG			6350	77.5	81	10080	72

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±10%.

The characteristics of the product listed above are subjected to change without notice.