



SI iBox

MAIN CHARACTERISTICS

Applications	Street and urban lighting
Optic	<p>STE-M/S: Asymmetrical optic for suburban street lighting. STU-M/S: Asymmetrical optic for street, urban and cycle-path lighting. STW: Asymmetrical optic for wide urban and suburban road lighting, specific for wet asphalts. SV/SV2: Asymmetrical optic for very narrow urban streets or highway entrance/exit turns. S05: Asymmetrical optic for street, urban and green areas lighting. S: Symmetrical optic for urban lighting and green areas. TS: Symmetrical optic for centre road lighting. Colour temperature: 4000K (3000K optional) CRI ≥ 70 Photobiological safety class: EXEMPT GROUP LED source efficiency: 168 lm/W @ 525mA, Tj=85°C, 4000K</p>
Insulation class	II, I
Protection degree	Optical unit: IP66 Driver: IP67 IK08
Dimensions	320x320x610mm
Weight	7.5 kg
Exposed surface	Side: 0.09m ² – Top: 0.10m ²
Installation	<p>SI08/09: Installation on pole 1/2" GAS male. SI06/10: suspended installation for 1/2" GAS female. (on chain) SI07/11: suspended installation for 1/2" GAS female. (on tige)</p>
Gear tray	Removable
Operating temp.	-40°C / +35°C
Storage temperature	-40°C / +80°C
Main reference	EN 60598-1, EN 60598-2-3, EN 62471, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3



ELECTRICAL CHARACTERISTICS

Rated voltage	220-240V 50/60Hz
Power factor	>0,9 (at full load)
Mains Connection	Cable: H05RN-F 2/3x1mm ² Optional: connector M/F IP66/68 for cables max. 2,5mm ² , Ø max. 12mm
Surge protection	CL. II: 8kV / 10kV CM/DM CL. I: 10kV / 10kV CM/DM (optional)
Control system (options)	<p>F: Fixed power not dimmable. DA: Automatic dimming (virtual midnight) with default profile. DAC: Custom DA profile. FLC: Constant light flux. D10: Dimming interface with 1-10V signal.</p>
Optical unit lifetime (Ta=25°C, 700mA)	>100.000hr L90B10 >100.000hr L90, TM-21

MATERIALS

Fixing	SI08/09: Steel powder painted. SI06/07/10/11: Stainless steel tube.
Body	SI06/07/08: Profiles: steel, upper dome: aluminium. SI09/10/11: Profiles: brass, upper dome: copper.
Optical unit body	Die-cast aluminum UNI EN1706 powder painted.
Optic	99.85% aluminum with a surface finish in 99.95% with vacuum-sealed deposition. Aluminum grade class A+ (DIN EN 16268)
Screen	Flat tempered glass, 4mm thickness PCG.
Colour	SI06/07/08: Graphite - Cod. 01 SI09/10/11: Brass





LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 4000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 4000K, lm)	RATED LED POWER* (Tj=85°C, W)
SI iBox 0F2H1 4.5-1M PCG	S05 STU-M STU-S	525	1430	16.5	86	2184	13
SI iBox 0F2H1 4.5-2M PCG	SV SV2 TS		2800	31	90	4368	26
SI iBox 0F2H1 4.7-1M PCG	S05 STU-M STU-S	700	1840	22	83	2765	17
SI iBox 0F2H1 4.7-2M PCG	SV SV2 TS		3590	41	87	5530	35
SI iBox 0F3 4.5-1M PCG	STE-M STE-S	525	1980	22	90	2950	17
SI iBox 0F3 4.5-2M PCG	STW		3920	40	98	5901	34
SI iBox 0F3 4.7-1M PCG	STE-M STE-S	700	2490	28.5	87	3735	23
SI iBox 0F3 4.7-2M PCG	STW		4960	53	93	7470	47
SI iBox 0F3 4.5-1M PCG	S05	525	1900	22	86	2950	17
SI iBox 0F3 4.5-2M PCG			3760	40	94	5901	34
SI iBox 0F3 4.7-1M PCG	S05	700	2390	28.5	83	3735	23
SI iBox 0F3 4.7-2M PCG			4760	53	89	7470	47
SI iBox 0F2H1 4.5-2M PCG	S	525	2800	31	90	4368	26
SI iBox 0F2H1 4.7-2M PCG	S	700	3590	41	87	5530	35

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±10%.

The characteristics of the product listed above are subjected to change without notice.



LUMINAIRE	OPTIC	LED CURRENT (mA)	RATED LUMINAIRE FLUX* (Tq=25°C, 3000K, lm)	RATED LUMINAIRE POWER* (Tq=25°C, Vin=230Vac, F/DA/DAC, W)	LUMINAIRE EFFICACY (Tq=25°C, lm/W)	RATED LED FLUX* (Tj=85°C, 3000K, lm)	RATED LED POWER* (Tj=85°C, W)
SI iBox 0F2H1 3.5-1M PCG	S05 STU-M STU-S	525	1330	16.5	80	1990	13
SI iBox 0F2H1 3.5-2M PCG	SV SV2 TS		2600	31	83	3981	26
SI iBox 0F2H1 3.7-1M PCG	S05 STU-M STU-S	700	1710	22	77	2520	17
SI iBox 0F2H1 3.7-2M PCG	SV SV2 TS		3340	41	81	5040	35
SI iBox 0F3 3.5-1M PCG	STE-M STE-S	525	1840	22	83	2701	17
SI iBox 0F3 3.5-2M PCG	STW		3650	40	91	5403	34
SI iBox 0F3 3.7-1M PCG	STE-M STE-S	700	2320	28.5	81	3420	23
SI iBox 0F3 3.7-2M PCG	STW		4610	53	86	6840	47
SI iBox 0F3 3.5-1M PCG	S05	525	1770	22	80	2701	17
SI iBox 0F3 3.5-2M PCG			3500	40	87	5403	34
SI iBox 0F3 3.7-1M PCG	S05	700	2220	28.5	77	3420	23
SI iBox 0F3 3.7-2M PCG			4430	53	83	6840	47
SI iBox 0F2H1 3.5-2M PCG	S	525	2600	31	83	3981	26
SI iBox 0F2H1 3.7-2M PCG	S	700	3340	41	81	5040	35

*RATED LUMINAIRE FLUX / RATED LUMINAIRE POWER: Rated data obtained in laboratory.

*RATED LED FLUX / RATED LED POWER: Rated data extrapolated from LED manufacturer datasheet.

Values indicated in this technical sheet are to be considered rated values. Flux tolerance: ±7%. Power tolerance: ±10%.

The characteristics of the product listed above are subjected to change without notice.